



NO	NAME OF PARTS	MATERIAL	QTY.
01	PUMP CASING	FC200	1
02	DRIVE GEAR	S45C	1SET
03	DRIVE GEAR	S45C	1SET
04	DRIVE SHAFT	S45C	1
05	DRIVE SHAFT	S45C	1
06	BEARING METAL A	CAC	1
07	BEARING METAL B	CAC	3
08	GEAR KEY A	S45C	1
09	GEAR KEY B	S45C	1
10	COUPLING KEY	S45C	1
11	COVER	FC200	1
12	SPRING PIN	SUS	1
13	BRACKET	FC200	2
14	OIL SEAL	NBR	1
15	STUD BOLT NUT	SS400	1
16	SPRING WASHER	SWP	16
17	BOLT	SS400	16
18	SHEET PACKING	OIL SHEET	4
19	SHEET PACKING	OIL SHEET	2
20	VALVE	CAC	1
21	SPRING	SUP	1
22	SPRING SHEET	S25C	1
23	VALVE COVER	FC200	1
24	LOCK NUT	SS400	1
25	SPINDLE	S25C	1
26	CAP	FC200	1
27	SHEET PACKING	OIL SHEET	1
28	COUPLING	FC200	1SET
29	HEXAGON SOCKET HEAD SCREW	SCM3	2
30	COUPLING PIN, NUT	S25C	4SET
31	COUPLING RING	NBR	4
32	MOTOR	-	1
33	VALVE CASE	FC200	1
34	BOLT WITH SPRING WASHER	S25C	4
35	BALL BEARING	SUJ	1
△36	WINDOW FRAME	SUS304	2
△37	BOLT	SS400	8
△38	WINDOW	ACRYLIC PLATE	2
△39	CROSS RECESSED TRUSS HEAD SCREW	SUS	8
△40	EYEBOLT	S20C	1
△41	BEARING COLLAR	C3604B	1

仕様 SPECIFICATION			
吐出量	CAPACITY	m <sup>3</sup> /H	7.5
吐出圧力	PRESSURE	MPa(kgf/cm <sup>2</sup> )	0.15 (1.5)
吸込揚程	SUCTION HEAD	m	3
回転速度	SPEED	min <sup>-1</sup> (rpm)	1740
電動機	MOTOR		4P, 2.2kW, AC440V, 60Hz
定格	RATING		連続 CONTINUOUS
電流	AMPERE		4.2A
絶縁	INSULATION CLASS		F
保護	PROTECTION		IP44
グラウンド	CABLE GLAND		20φ
ポンプメーカー	PUMP MAKER		SANSRIN ELECTRIC CORPORATION
ヤンマーコード	YANMAR CODE		43600-039210

VGR40 (φ3, AC440V, 60Hz)  
 潤滑油プライミングモーターポンプ  
 L.O. PRIMING MOTOR PUMP

ヤンマーパワーテクノロジー株式会社 DWG. B4-00003-1020  
 YANMAR POWER TECHNOLOGY CO., LTD. No. △